

Capacity 1,000 gallons
Dimensions,	length 14'7" overall width 8'2" height 85 ½"
Underclearance 14" at axle
Weight,	empty 2,540 lbs loaded 10,540 lbs
GVWR 12,000 lbs
Recommended towing vehicle one ton or larger	
Axle tandem 6,000 lbs
Brakes electric on both axles
Wheels eight hole rims
Hitch adjustable 12,000 lbs rated Bulldog coupler with 2 5/16" ball
Tires 7.50 x 16 LT
Jackstand side-mount crank style, 12,000 lbs rated
Suspension five leaf slipper
Frame 6" channel steel saddle for tank support
Tank	Polyethylene 3/8" thick, elliptical design 16" manhole with 4" vent cap Drain holes at bottom for cleaning Baffles molded into sides of tank Repairable and recyclable
Pump / engine Multiquip QP204H 2" centrifugal 4.0 hp Honda engine with low oil alert "shut down"Discharge rate 142 GPM

Control manifold	<p>.....control all functions with 5 brass valves</p> <p>.....simple to use numbered valves make operation a snap</p>
Plumbing	<p>.....self-loading feature is standard feature</p> <p>.....2" pipe feeds dual rear spray heads</p> <p>.....1 1/2" fire hose hook up,</p> <p>..... garden hose faucet</p> <p>..... 2" rear hydrant fill assembly</p> <p>..... Safety valve to prevent destructive "water hammer" feedback</p>
Lights	<p>.....recessed and DOT approved</p>
Safety chains	<p>..... two provided with clevis hooks</p>