

Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

Waterdog 525-Gallons "Potable Water Pumper" Water Trailer



General Description

The Waterdog is a durable, industrial-grade product that is built to last. Our trailers are utilized by the government and military and are constructed to perform and excel in day-to-day operations. This trailer will be manufactured per your exact specifications to accomplish any task you need, whether that be dust/allergen control, agricultural spraying, cleaning of equipment, emergency fire-fighting, or to secure a means of transporting potable (NSF-61) water.

www.ciequip.com



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

Frame Specs:

Axles	Dexter Leaf-Spring 3500LB axles
Axies	
	74" hub face
	Electric brakes
	545 hub/drum
Tires and Wheels	ST205/75D15
Hitch	2" Height Adjustable Bulldog Type Coupler
Jack	7000lb Adjustable Swivel Jack
DOT Approval	LED Recessed Lighting
	Reflective Stickers
	Electric Brakes
	Brake Away System
	Safety Chain Kit
	License Plate Mount and Light
Material	5" Steel Channel. Deck designed specifically for
	corresponding tank.
Color	Industrial Charcoal Grey (Customizable)
Fenders	Custom Heavy-Duty Diamond Plated
Dimensions	L x W x H, approximately 151" x 80" x 88"
Weight	Approximately 1600lbs unloaded, 5978lbs
Warranty	1 Year Manufacturers Warranty

Tank Specs:

Capacity	525-gallons
Color	Translucent White, or Black
Material	Polyethylene
NSF-61 Approval	Yes
Gallon Indicators	Yes
Inlet	16" threaded, vented manhole. All models
	include a vented lid, potable lid will also be
	lockable.
Outlet	2" NPT Bulkhead Fitting
Bands	(2) Support bands will fasten the tank to the
	trailer
Dimensions	L x W x H, 71" x 49" x 54"
Warranty	3 Year Manufacturers Warranty

www.ciequip.com



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

Pump Specs:

Table 133	
· · ·	- ·
Max. Lift	25 ft
Max. Head	115 ft
Max. Pressure	49.8 psi
Powered by 3.5HP GX1	L20 Honda gasoline engine
1 Year Manufactures V	Varrenty
Max. Water Capacity	106 gpm
Max. Lift	25 ft
Max. Head	246 ft
Max. Pressure	106.4 psi
Powered by 4.8HP Hor	nda GX160 gasoline engine.
1 Year Manufactures V	Varranty
Max. Water Capacity	180 gpm
Max. Lift	20 ft
Max. Head	78 ft
Max. Pressure	34 psi
Powered by 5.0HP Hor	nda GX160 gasoline engine.
1 Year Manufacturers Warranty	
Max. Water Capacity	32gpm
Max. Lift	26ft
Max. Head	121ft
Max Pressure	52psi
Powered by GX25 gaso	oline engine.
1 Year Manufacturers	
	Max. Head Max. Pressure Powered by 3.5HP GXX 1 Year Manufactures V Max. Water Capacity Max. Lift Max. Head Max. Pressure Powered by 4.8HP Hor 1 Year Manufactures V Max. Lift Max. Head Max. Pressure Powered by 5.0HP Hor 1 Year Manufacturers V Max. Lift Max. Pressure Powered by 5.0HP Hor 1 Year Manufacturers V Max. Water Capacity Max. Lift Max. Head Max. Pressure Powered by GX25 gasc Powered by GX25 gasc



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

Features for Non-Potable: (NOTE: Different models contain different features)

Self-Loading (Drafting) Kit	2" Kit Which Includes the 2" x 25' Suction Hose, and Strainer.
Tank Manhole	16" Overhead Fill equipped with lid. Potable lid will include NSF-61 Rated lockable hinged.
Hydrant Fill Kit	2 ½" Kit Which Includes the 2 ½" x 25' Hydrant hose, and Hydrant Wrench
Dual-Headed Rear-Spray Bar	Galvanized 2" Steel pipe with (2) galvanized silted caps
1" X 100' Coxhose Reel	1" x 100' hose fixated on the hand crank Coxhose reel.
Side Manifold	-1 ½" Camlock discharge connection for the included 1 ½" x 50' fire hose and adjustable fog nozzle -3/4" Hose Bib -Check Valve -2" Control valve for Rear Spray Bar
Hose Box	Fender Mounted Lockable Hose Box: Storage Solution for Hoses and Accessories

Features for Potable: (NOTE: Different models contain different features)

Food-Grade Hydrant Fill Kit	2 ½" Kit which Includes the 2 ½" x 25' Food Grade Hydrant Hose and Hydrant Wrench
Side Manifold	-1 ½" Camlock Discharge Connection with Included Food-Grade 1 ½" x 25' Fire hose and adjustable Fog Nozzle -¾" Hose bib with vacuum break -Check Valve
Zero-Drain	Installed at bottom of tank to ensure proper cleaning and flushing
¾" Gravity-Fed Hose Bib	Rear-Facing Hose Bib to Gravity Fed Water Out of Tank
Hose Box	Fender Mounted Lockable Hose Box: Storage Solution for Hoses and Accessories

www.ciequip.com



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38th St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

Optional Add-Ons:

Hose Holder	Steel Welded Hose Holder Mounted on the
	Frame
Side Spray Attachment	Silted cap attachment to connect to side manifold
Spare Tire + Welded Carrier	Custom welded carrier mounted to the frame
	with spare tire
Electric Valve	Electric Valve To Control RSB from Towing
	Vehicle
Military Spigot Array	(4) ¾" Gravity Fed Hose Bibs