

Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38<sup>th</sup> St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

### Waterdog 525-Gallons "Potable Water Transporter" Water Trailer



### **General Description**

The Waterdog is a durable, industrial-grade product that is built to last. Our trailers are utilized by the government and military and are constructed to perform and excel in day-to-day operations. This trailer will be manufactured per your exact specifications to accomplish any task you need, whether that be dust/allergen control, agricultural spraying, cleaning of equipment, emergency fire-fighting, or to secure a means of transporting potable (NSF-61) water.

#### www.ciequip.com



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38<sup>th</sup> St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

### Frame Specs:

Axles	Dexter Leaf-Spring 3500LB axles
Axies	
	74" hub face
	Electric brakes
	545 hub/drum
Tires and Wheels	ST205/75D15
Hitch	2" Height Adjustable Bulldog Type Coupler
Jack	7000lb Adjustable Swivel Jack
DOT Approval	LED Recessed Lighting
	Reflective Stickers
	Electric Brakes
	Brake Away System
	Safety Chain Kit
	License Plate Mount and Light
Material	5" Steel Channel. Deck designed specifically for
	corresponding tank.
Color	Industrial Charcoal Grey (Customizable)
Fenders	Custom Heavy-Duty Diamond Plated
Dimensions	L x W x H, approximately 151" x 80" x 88"
Weight	Approximately 1600lbs unloaded, 5978lbs
Warranty	1 Year Manufacturers Warranty

#### Tank Specs:

Capacity	525-gallons
Color	Translucent White, or Black
Material	Polyethylene
NSF-61 Approval	Yes
Gallon Indicators	Yes
Inlet	16" threaded, vented manhole. All models
	include a vented lid, potable lid will also be
	lockable.
Outlet	2" NPT Bulkhead Fitting
Bands	(2) Support bands will fasten the tank to the
	trailer
Dimensions	L x W x H, 71" x 49" x 54"
Warranty	3 Year Manufacturers Warranty

### www.ciequip.com



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38<sup>th</sup> St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

### **Pump Specs:**

Standard Pump: Multiquip QP2H	Max. Water Capacity	142 gpm		
	Max. Lift	25 ft		
	Max. Head	115 ft		
	Max. Pressure	49.8 psi		
		120 Honda gasoline engine		
	1 Year Manufactures \	1 Year Manufactures Warrenty		
Upgraded Pump: Multiquip QP205SH	Max. Water Capacity	106 gpm		
	Max. Lift	25 ft		
	Max. Head	246 ft		
	Max. Pressure	106.4 psi		
	Powered by 4.8HP Ho	nda GX160 gasoline engine.		
	1 Year Manufactures \	1 Year Manufactures Warranty		
NSF-61-Rated Pump	Max. Water Capacity	180 gpm		
	Max. Lift	20 ft		
	Max. Head	78 ft		
	Max. Pressure	34 psi		
	Powered by 5.0HP Honda GX160 gasoline engine.			
	1 Year Manufacturers	1 Year Manufacturers Warranty		
Honda WX10 Pump	Max. Water Capacity	32gpm		
	Max. Lift	26ft		
	Max. Head	121ft		
	Max Pressure	•		
	Powered by GX25 gase	oline engine.		
	1 Year Manufacturers	Warranty		



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38<sup>th</sup> St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

#### Features for Non-Potable: (NOTE: Different models contain different features)

6 16 : 1: /5 6:: \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
Self-Loading (Drafting) Kit	2" Kit Which Includes the 2" x 25' Suction Hose,
	and Strainer.
<mark>Tank Manhole</mark>	16" Overhead Fill equipped with lid. Potable lid
	will include NSF-61 Rated lockable hinged.
Hydrant Fill Kit	2 ½" Kit Which Includes the 2 ½" x 25' Hydrant
	hose, and Hydrant Wrench
Dual-Headed Rear-Spray Bar	Galvanized 2" Steel pipe with (2) galvanized silted
	caps
1" X 100' Coxhose Reel	1" x 100' hose fixated on the hand crank Coxhose
	reel.
Side Manifold	-1 ½" Camlock discharge connection for the
	included 1 ½" x 50' fire hose and adjustable fog
	nozzle
	-3/4" Hose Bib
	-Check Valve
	-2" Control valve for Rear Spray Bar
Hose Box	Fender Mounted Lockable Hose Box: Storage
	Solution for Hoses and Accessories

#### **Features for Potable: (NOTE: Different models contain different features)**

Food-Grade Hydrant Fill Kit	2 ½" Kit which Includes the 2 ½" x 25' Food Grade Hydrant Hose and Hydrant Wrench
Side Manifold	-1 ½" Camlock Discharge Connection with Included Food-Grade 1 ½" x 25' Fire hose and adjustable Fog Nozzle -¾" Hose bib with vacuum break -Check Valve
Zero-Drain	Installed at bottom of tank to ensure proper cleaning and flushing
3/4" Gravity-Fed Hose Bib	Rear-Facing Hose Bib to Gravity Fed Water Out of Tank
Hose Box	Fender Mounted Lockable Hose Box: Storage Solution for Hoses and Accessories

### www.ciequip.com



Mail – P.O. Box 18985 – Tucson, Arizona 85731 Shipping – 3841 E 38<sup>th</sup> St. Tucson, AZ 85713 Office – 520.579.7458 Fax – 520.579.7439

#### **Optional Add-Ons:**

Hose Holder	Steel Welded Hose Holder Mounted on the
	Frame
Side Spray Attachment	Silted cap attachment to connect to side manifold
Spare Tire + Welded Carrier	Custom welded carrier mounted to the frame
	with spare tire
Electric Valve	Electric Valve To Control RSB from Towing
	Vehicle
Military Spigot Array	(4) ¾" Gravity Fed Hose Bibs